



HANGIL HC Co., Ltd.
Traffic System Specialized Enterprise

Approx. 32%

less power consumption compared to
the lowest power-consuming
products from competitors



Walk Safely and Save Energy!

Energy Efficient Embedded In-Ground Pedestrian Signal Light



Public Procurement Service
Registration (MAS)



Certificate of Conformity for
Broadcasting and
Communication Equipment



Certificate of Traffic Signal Controller
Functional Inspection



Approval of the National Police Agency
Standard Guidelines for Traffic Safety
Facilities

HANGIL HC Co., Ltd.

Energy Efficient

Embedded In-Ground Pedestrian Signal Light

Pedestrian safety system that visually guides pedestrians to wait or cross the road preventing traffic accidents. The system operates by synchronizing the embedded in-ground signal light with the crosswalk pedestrian signal light. It perfectly prevents thermal deformation and leakage. The power consumption is reduced to 1.8W for energy efficiency!


HANGIL HC's embedded in-ground pedestrian signal light enhances efficiency while maintaining the advantages of existing products, is environmentally friendly and ensures safe crosswalking!

Product Competitiveness

Energy Efficient

Maximize energy efficiency with the lowest power consumption in the industry

HANGIL HC's embedded in-ground pedestrian signal light boasts the lowest power consumption in the industry, consuming approximately 32% less power than the lowest power-consuming products from competitors.



Source: Korea ON-Line E-Procurement Market
by Public Procurement Service


Save energy consumption by automatically adjusting day/nighttime brightness

Reduce unnecessary power consumption while maintaining visibility by automatically adjusting brightness accordingly for day/nighttime using a photoresistor.



Save energy and maintain visibility by varying the lighting ON/OFF pattern for a set timeframe



Allows alternating the odd and even lighting patterns for a set timeframe by client request, for further energy saving. You can also reduce power consumption while maintaining visibility, this by selectively turning on the display units individually rather than turning on all at once.



Improved Visibility

Increased brightness by combining SMD LEDs and lenses

It focuses light with a lens over the SMD LED on the display unit, which enables higher brightness with the same power consumption, providing clearer signal information to both pedestrians and drivers by ensuring visibility.



Strong Durability

Improved strong durability with stable fixation

Securely fixed to the ground with bracket supports and hinges, it offers excellent durability against external impacts and weather changes.



Improved device durability with waterproof and condensation resistance


The epoxy-filled display unit delivers a waterproof effect. The space secured under the bracket offers protection against rainwater and condensation, which reduces device failure and prolongs the device's life.



Optimized Installation

Installation flexibility optimized for various environments

Installation in straight lines as well as smooth curves and slopes is possible by adding additional brackets using hinges, which improve displacement and twisting prevention.



Product Specifications



Display Unit

A device installed behind the curb of a crosswalk that indicates the pedestrian light status as green, flashing green, or red

• Model	HGHC-24DE1
• Dimensions	300×100×60mm
• Power Consumption	1.8W
• Input Voltage	24DCV
• Weight	1.45kg

Control Unit

device that controls day nighttime lighting by collecting pedestrian light status from the traffic signal controller External Device Integrated Interface Board

• Model	HGHC-24CE1
• Dimensions	300×250×160mm
• Input Voltage	220ACV
• Weight	5.1kg

External Device Integrated Interface Board

A device that is connected to a standard traffic signal controller to transmit a pedestrian signal to the control unit in real time


• Model	HGHC-24EDIB01
• Dimensions	233×160mm
• Weight	0.20kg



Integrated Management System (IMS)

Detection of auxiliary device failure

Monitor the operating status of traffic safety facilities in real-time via an integrated gateway to collect relevant information when failures occur.




Auxiliary device failure
Real-time collection of failing device
Remote repairment of faulty device



Traffic Information Center - Remote Control Access

Remotely control and repair when failures occur by monitoring traffic safety facilities at all intersections in the local government in real-time.



HANGIL HC Co., Ltd.

Office. F410~413, 602~603, 325 Sandan-ro, Danwon-gu, Ansan-si, Gyeonggi-do, Republic of Korea Zip Code:15426

Tel: (+82) 31-431-2005 (0688) | Email: 2hg@hangilhc.com | Website: www.hangilhc.com

Factory 1: 45 Anseongmatchum-daero, Seoun-myeon, Anseong-si, Gyeonggi-do, Republic of Korea |

Factory 2: 732 Seongjin-ro, Ipjang-myeon, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea

